



LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

POWER STEERING FLUID WITH CONDITIONERS



Lucas Oil Power Steering Fluid with Conditioners is a premium power steering fluid meeting most OEM power steering fluid requirements for automotive and pickup truck power steering systems. It is specially formulated to add lubricity and to help stop wear for long lasting performance. Lucas Oil Power Steering Fluid with Conditioners is specially formulated with improved shear stability, oxidation, and seal compatibility to deliver maximum performance in all power steering systems. Our reduced friction formula maintains smooth power steering operation and keeps internal springs and valves clean to eliminate sticking and helps stop pump squealing. Our high viscosity index fluid maintains fluidity at low temperatures, ensuring smooth operation during cold starts and normal driving alike.

PART NUMBER AND SIZE:

10442 - 16 Ounce (Case of 12)
10442-8 - 16 Ounce (Case of 8)

FEATURES AND BENEFITS:

- Improves steering response and feel.
- Extends life of pumps, rack and pinion gears, seals, cylinders, and valves.
- Compatible with all power steering systems and fluids, petroleum or synthetic
- Reduces and prevents power steering system leaks due to worn elastomer seals.
- Suitable for use in Honda or Accura Power Steering Systems.

SPECIFICATIONS, APPROVALS AND RECOMMENDATIONS:

Suitable for use for Ford, General Motors, Stellantis, Toyota and most other makes and models. Meets or exceeds: Ford ESW-M2C128-CD / M2C138-CJ / M2C195-A / M2C33-F; GM 9985010; Navistar TMS6810; VW TL-VW-570-26; Navistar TMS6810; Chrysler MS-1872/MS-5931/MS-9602; American Motor Corp C4124; BMW 83 29 0 429 576; Hyundai/Kia PSF-3; MB236.3; Mitsubishi Diamond PSF/SP III; Nissan PSF-II; Saab 30 32 380; Subaru K0209A0080; ZF 09

MAIN APPLICATIONS:

Suitable for use in virtually all makes and models, foreign and domestic.



LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

TYPICAL PHYSICAL CHARACTERISTICS:

PROPERTIES	ASTM	TYPICAL
API Gravity	D402	34.1
Specific Gravity @ 60°F	D4052	0.854
Density @ 60°F, Lbs/US Gal	D4052	7.12
Viscosity @ 40°C cSt	D445	51.7
Viscosity @ 100°C cSt	D445	10.4
Color	Visual	Amber
Flash Point, COC @ °F	D92	475
Viscosity Index	D2270	195

These characteristics are typical of current production. However, slight variations in these characteristics may occur.

LINKS AND ADDITIONAL INFORMATION:

For additional product or health and safety information, including product Safety Data Sheets, visit [LucasOil.com](https://www.LucasOil.com)