

SECTION 1 Identification**1.1. GHS Product identifier**

Product form : Mixture
Product name : Synthetic SAE 0W-20 Motor Oil
Type of product : Lubricating oil
Part Number : 28003

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN, 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924
International: 1-813-248-0585
(collect calls accepted)

SECTION 2 Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS CA)**

Not classified

2.2. GHS label elements, including precautionary statements**GHS CA labelling**

No labelling applicable

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients**3.1. Substances**

Not applicable

Synthetic SAE 0W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	80 - 100*	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	3 - 7*	Asp. Tox. 1, H304

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

*Contains fixed concentration

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures general	: If you feel unwell, seek medical advice.
Self protection of the first-aiders	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
-------------	-------------------

Synthetic SAE 0W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.
For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Keep cool. Protect from sunlight.
Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Synthetic SAE 0W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Colourless
Odour	: Mixture contains one or more component(s) which have the following odour:
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.845
Density	: 7.055 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 46.27 mm ² /s @ 40 ° C
Explosive limits	: No data available
Particle characteristics	: Particle size : Not Applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

Synthetic SAE 0W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE CA (oral)	5000 mg/kg bodyweight
ATE CA (Dermal)	5000 mg/kg bodyweight

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard	: Not classified.
-------------------	-------------------

Synthetic SAE 0W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Synthetic SAE 0W-20 Motor Oil	
Viscosity, kinematic	46.27 mm ² /s @ 40 ° C
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Viscosity, kinematic	12 mm ² /s
Hydrocarbon	Yes
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm ² /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : None under normal conditions.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified.
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

12.2. Persistence and degradability

Synthetic SAE 0W-20 Motor Oil	
Persistence and degradability	Not rapidly degradable
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable

Synthetic SAE 0W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.3. Bioaccumulative potential

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

TDG
Not regulated

DOT
Not regulated

Synthetic SAE 0W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16 Other Information

Issue date : 06/07/2025

Revision date : 07/23/2025

Supersedes : 06/07/2025

Full text of hazard classes and H-statements:

H304	May be fatal if swallowed and enters airways
------	--

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.