

**Safety Data Sheet**

according to the Hazardous Products Regulation (WHMIS 2015)

Issue date: 06/10/2025 Revision date: 09/24/2025 Supersedes: 07/16/2025 Version: 3.0

**SECTION 1 Identification****1.1. GHS Product identifier**

Product form : Mixture  
Product name : Hot Rod & Classic SAE 20W-50 Motor Oil  
Type of product : Lubricating oil  
Part Number : 28027

**1.2. Other means of identification**

No additional information available

**1.3. Recommended use of the chemical and restrictions on use**

Use of the substance/mixture : Lubricating oil

**1.4. Supplier's details**

Lucas Oil Products, Inc.  
3199 Harrison Way NW  
Corydon, IN, 47112  
USA  
T 800-342-2512  
[sds@lucasoil.com](mailto:sds@lucasoil.com) - [www.LucasOil.com](http://www.LucasOil.com)

**1.5. Emergency phone number**

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week  
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924  
International: 1-813-248-0585  
(collect calls accepted)

**SECTION 2 Hazard identification****2.1. Classification of the substance or mixture****Classification (GHS CA)**

Skin sensitization, Category 1 H317 May cause an allergic skin reaction.  
Full text of H-statements: see section 16

**2.2. GHS label elements, including precautionary statements****GHS CA labelling**

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Warning

Hazard statements (GHS CA) :

Precautionary statements (GHS CA) :

H317 - May cause an allergic skin reaction  
P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P321 - Specific treatment (see supplemental first aid instruction on this label).

# Hot Rod & Classic SAE 20W-50 Motor Oil

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	65 - 85*	Asp. Tox. 1, H304
Paraffin oils (petroleum), catalytic dewaxed heavy	Paraffin oils (petroleum), catalytic dewaxed heavy Paraffin oils (petroleum), catalytic dewaxed heavy	CAS-No.: 64742-70-7	5 - 10*	Asp. Tox. 1, H304
Molybdenum, bis[O,O-bis(2-ethylhexyl)phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo)	Molybdenum, bis[O,O-bis(2-ethylhexyl)phosphorodithioato-S]dioxodi-mu-thioxodi-	CAS-No.: 72030-25-2	0.5 - 1.5*	Skin Irrit. 2, H315 Skin Sens. 1, H317

\*Chemical name, CAS number and/or exact concentration have been withheld as CBI

\*Contains fixed concentration

## SECTION 4 First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures general	: If you feel unwell, seek medical advice.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

# Hot Rod & Classic SAE 20W-50 Motor Oil

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

## SECTION 5 Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
Environmental precautions	: Avoid release to the environment.

### 6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

# Hot Rod & Classic SAE 20W-50 Motor Oil

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep cool. Protect from sunlight.
Packaging materials	: Store always product in container of same material as original container.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless dark green White to grey
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Characteristic odour Almost odourless
Odour threshold	: No data available

# Hot Rod & Classic SAE 20W-50 Motor Oil

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.88
Density	: 7.3522 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 166.6 mm <sup>2</sup> /s @ 40 ° C
Explosive limits	: No data available
Particle characteristics	: Particle size : Not Applicable

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

## SECTION 11 Toxicological information

### 11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

# Hot Rod & Classic SAE 20W-50 Motor Oil

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

### Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified.

### Hot Rod & Classic SAE 20W-50 Motor Oil

Viscosity, kinematic	166.6 mm <sup>2</sup> /s @ 40 ° C
----------------------	-----------------------------------

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Viscosity, kinematic	18 mm <sup>2</sup> /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : None under normal conditions.

## SECTION 12 Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

### 12.2. Persistence and degradability

#### Hot Rod & Classic SAE 20W-50 Motor Oil

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

# Hot Rod & Classic SAE 20W-50 Motor Oil

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) (72030-25-2)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified  
Fluorinated greenhouse gases : No

## SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.

## SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

### 14.6. Special precautions for user

**TDG**  
Not regulated

# Hot Rod & Classic SAE 20W-50 Motor Oil

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### DOT

Not regulated

### IMDG

Not regulated

### IATA

Not regulated

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78<sup>9</sup> and the IBC Code<sup>10</sup>

Not applicable

## SECTION 15 Regulatory information

### Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

Listed on the Canadian DSL (Domestic Substances List)

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

### Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) (72030-25-2)

Listed on the Canadian DSL (Domestic Substances List)

### Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) (72030-25-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

## SECTION 16 Other Information

Issue date : 06/10/2025  
Revision date : 09/24/2025  
Supersedes : 07/16/2025

### Full text of hazard classes and H-statements:

H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.