



LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

SAE 80W-90 GEAR OIL

Lucas Oil SAE 80W-90 Gear Oil is a premium lubricant specially formulated for final drives, axles, and differentials in passenger cars and heavy-duty equipment. It is formulated with powerful anti-wear and extreme pressure additives to prevent scuffing and premature failure of all gear types in the most demanding service conditions. Our specialty formulation is yellow metal safe, and clings to gear teeth to ensure they are never starved for lubrication. Our formulation is shear stable and will retain viscosity for long fluid life and maximum protection. Lucas Oil SAE 80W-90 Gear Oil is stable under high-torque and high temperature conditions but remains fluid at extremely cold temperatures to ensure excellent lubrication no matter the weather. It is fortified with seal conditioners that keep seals supple, preventing leaks and extending service life. Our formulation contains an embedded friction modifier for use in standard or limited slip differentials.

Recommended by Lucas Oil for any application requiring SAE 80W-90 gear oil, whether in light duty trucks, SUVs, or commercial vehicles. Meets or exceeds API GL-5, MT-1, and other common gear oil specifications.

PART NUMBER AND SIZE:

20043 – 1 Quart
20046 – 1 Gallon
20066 – 5 Gallon
20069 – 55 Gallon Drum

FEATURES AND BENEFITS:

- Fortified with anti-foaming agents to prevent cavitation at high RPM's.
- Safely blends with all other gear oils and additives.
- Shear stable, long-lasting formula.
- High-performance, extreme pressure protection
- Suitable for standard or limited slip differentials.

SPECIFICATIONS, APPROVALS AND RECOMMENDATIONS:

Meets or exceeds API GL-5, API MT-1, SAE J2360, MIL-PRF-2105E, MACK GO-J, PG-2 Limited Slip.

MAIN APPLICATIONS:

For use wherever SAE 80W-90 GL-5 Gear Oil is recommended by the original equipment manufacturer, commonly: differentials and axles of light and heavy-duty trucks, SUVs, cars with rear drive and both front and rear differentials of 4X4's.



LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

TYPICAL PHYSICAL CHARACTERISTICS:

PROPERTIES	ASTM	TYPICAL
API Gravity	D4052	25.0
Specific Gravity @ 60°F	D4052	0.9042
Density @ 60°F, Lbs/US Gal	D4052	7.529
Viscosity @ 100°C cSt	D445	15.0
Color		Clear Light Amber
Flash Point, COC @ °F	D92	430
Pour Point, °C (°F)	D97	-36 (-33)

These characteristics are typical of current production. However, slight variations in these characteristics may occur.

LINKS AND ADDITIONAL INFORMATION:

For additional product or health and safety information, including product Safety Data Sheets, visit LucasOil.ca