

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Issue date: 04/29/2025 Revision date: 05/27/2026 Supersedes: 02/04/2026 Version: 6.0

SECTION 1 Identification**1.1. GHS Product identifier**

Product form : Mixture
Product name : Semi-Synthetic 2-Cycle Land & Sea Oil
Part Number : 20467

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : lubricants
Recommended use : lubricants

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2 Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS CA)**

Hazardous to the aquatic environment, Chronic Hazard, Category 4 H413 May cause long lasting harmful effects to aquatic life.
Full text of H-statements: see section 16

2.2. GHS label elements, including precautionary statements**GHS CA labelling**

Hazard statements (GHS CA) : H413 - May cause long lasting harmful effects to aquatic life
Precautionary statements (GHS CA) : P273 - Avoid release to the environment.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	45 - 70*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Distillates (petroleum), hydrotreated light	Distillates (petroleum), hydrotreated light distillates (petroleum), hydrotreated light / kerosine - unspecified	CAS-No.: 64742-47-8	15 - 40*	Asp. Tox. 1, H304
White mineral oil (petroleum)	White mineral oil (petroleum) mineral oil (petroleum), white / purity FG WO 35 / purity FG WO 90 / shell on dina 917 / shell risella 917 / slab oil (obs.) / white mineral oil / white mineral oil (petroleum)	CAS-No.: 8042-47-5	0.5 - 1.5*	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic	Distillates (petroleum), solvent-dewaxed light paraffinic distillates (petroleum), solvent-dewaxed light paraffinic	CAS-No.: 64742-56-9	< 100	Asp. Tox. 1, H304

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

*Contains fixed concentration

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Immediately call a POISON CENTER/doctor. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: If medical advice is needed, have product container or label at hand. Call a physician immediately.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause shortness of breath, tightness of the chest, a sore throat and cough.
Symptoms/effects after skin contact	: Causes skin irritation. Redness. Itching.
Symptoms/effects after eye contact	: Causes serious eye irritation. Blurred vision. redness, itching, tears.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Ingestion may cause nausea and vomiting. Abdominal pain.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Evacuate area. Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material. Move containers from spill area. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Do not breathe vapours.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep only in the original container in a cool, well-ventilated place away from: Direct sunlight, Heat sources. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.858
Density	: 7.167 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 40.13 mm ² /s @ 40 °C
Explosive limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hardening time: : No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit > 5000 mg/kg Source: IUCLID

Distillates (petroleum), hydrotreated light (64742-47-8)

LD50 oral rat > 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)

LD50 oral 15000 mg/kg

LD50 dermal rabbit > 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

LC50 Inhalation - Rat > 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -

LC50 Inhalation - Rat (Dust/Mist) > 5.2 mg/l Source: IUCLID

ATE CA (oral) 15000 mg/kg bodyweight

White mineral oil (petroleum) (8042-47-5)

LD50 oral rat > 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s))

LD50 dermal rabbit > 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))

LC50 Inhalation - Rat > 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol), 14 day(s))

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

LD50 oral rat > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

LD50 dermal rabbit > 2000 mg/kg Source: EHCA

Skin corrosion/irritation : Not classified

White mineral oil (petroleum) (8042-47-5)

pH Not applicable (non-soluble in water)

Serious eye damage/irritation : Not classified

White mineral oil (petroleum) (8042-47-5)

pH Not applicable (non-soluble in water)

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)

NOAEL (animal/male, F0/P) ≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

White mineral oil (petroleum) (8042-47-5)	
NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified.

Semi-Synthetic 2-Cycle Land & Sea Oil	
Viscosity, kinematic	40.13 mm ² /s @ 40 °C

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm ² /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

White mineral oil (petroleum) (8042-47-5)	
Viscosity, kinematic	3 – 20.5 mm ² /s (40 °C, ISO 3104: Determination of kinematic viscosity and calculation of dynamic viscosity, Niet experimenteel bepaald; afgeleid van de indeling)

Symptoms/effects after inhalation : May cause drowsiness or dizziness. May cause shortness of breath, tightness of the chest, a sore throat and cough.
Symptoms/effects after skin contact : Causes skin irritation. Redness. Itching.
Symptoms/effects after eye contact : Causes serious eye irritation. Blurred vision. redness, itching, tears.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Ingestion may cause nausea and vomiting. Abdominal pain.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : May cause long lasting harmful effects to aquatic life.
Hazardous to the aquatic environment, short-term (acute) : Not classified

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hazardous to the aquatic environment, long-term (chronic) : May cause long lasting harmful effects to aquatic life.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

12.2. Persistence and degradability

Semi-Synthetic 2-Cycle Land & Sea Oil	
Persistence and degradability	Biodegradability in water: no data available.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Not rapidly degradable
White mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water.
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Semi-Synthetic 2-Cycle Land & Sea Oil	
Bioaccumulative potential	No data available concerning bioaccumulation.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Distillates (petroleum), hydrotreated light (64742-47-8)	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
White mineral oil (petroleum) (8042-47-5)	
Bioaccumulative potential	Potential for bioaccumulation ($500 \leq BCF \leq 5000$).
BCF - Other aquatic organisms [1]	1216 l/kg (BCFBFAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.2 (Experimental value)
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

12.4. Mobility in soil

Semi-Synthetic 2-Cycle Land & Sea Oil	
Ecology - soil	No additional information available.
White mineral oil (petroleum) (8042-47-5)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

White mineral oil (petroleum) (8042-47-5)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.6 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	--

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

TDG

Not regulated

DOT

Not regulated

IMDG

Not regulated

IATA

Not regulated

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

White mineral oil (petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Listed on the Canadian DSL (Domestic Substances List)

Semi-Synthetic 2-Cycle Land & Sea Oil

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

White mineral oil (petroleum) (8042-47-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

SECTION 16 Other Information

Issue date : 04/29/2025
Revision date : 05/27/2026
Supersedes : 02/04/2026

Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Semi-Synthetic 2-Cycle Land & Sea Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Full text of hazard classes and H-statements:	
H304	May be fatal if swallowed and enters airways
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.