

**SECTION 1 Identification****1.1. GHS Product identifier**

Product form : Mixture  
Product name : Slick Mist Tire & Trim Shine  
Part Number : 20513

**1.2. Other means of identification**

No additional information available

**1.3. Recommended use of the chemical and restrictions on use**

Use of the substance/mixture : Automotive Care Products.

**1.4. Supplier's details**

Lucas Oil Products, Inc.  
3199 Harrison Way NW  
Corydon, IN 47112  
USA  
T 800-342-2512  
[sds@lucasoil.com](mailto:sds@lucasoil.com) - [www.LucasOil.com](http://www.LucasOil.com)

**1.5. Emergency phone number**

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

**SECTION 2 Hazard identification****2.1. Classification of the substance or mixture****Classification (GHS CA)**

Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment, Acute Hazard, Category 2	H401	Toxic to aquatic life.
Hazardous to the aquatic environment, Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H-statements: see section 16

**2.2. GHS label elements, including precautionary statements****GHS CA labelling**

Hazard pictograms (GHS CA) : 

Signal word (GHS CA) : Warning

Hazard statements (GHS CA) : H317 - May cause an allergic skin reaction  
H361 - Suspected of damaging fertility or the unborn child  
H401 - Toxic to aquatic life  
H412 - Harmful to aquatic life with long lasting effects

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS CA) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P308+P313 - IF exposed or concerned: Get medical advice or attention.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidyl) ester bis(1,2,2,6,6-pentamethyl-4-piperidyl) decanedioate / bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate / decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidyl) ester / tinuvin 292	CAS-No.: 41556-26-7	0.5 - 1.5*	Skin Sens. 1, H317 Repr. 2, H361 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS-No.: 82919-37-7	0.1 - 1*	Skin Sens. 1, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
D-Limonene	d-Limonene	CAS-No.: 5989-27-5	0.004 - 0.114	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

	(+)-1-methyl-4-isopropenyl-1-cyclohexene / (+)-4-isopropenyl-1-methylcyclohexene / (+)-cajuputene / (+)-carvene / (+)-citrene / (+)-para-mentha-1,8-diene / (+)-p-mentha-1,8-diene / (+)-R-limonene / (R)-(+)-4-isopropenyl-1-methyl-1-cyclohexene / (R)-(+)-limonene / (R)-1-methyl-4-(1-methylethenyl)cyclohexene / (R)-4-isopropenyl-1-methyl-1-cyclohexene / (R)-p-mentha-1,8-diene / 1,8-menthadiene, D- / 1-methyl-4-(1-methylethenyl)cyclohexene, (R)- / cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)- / cyclohexene, 1-methyl-4-(1-methylethenyl)-, (theta)- / cyclohexene, 4-isopropenyl-1-methyl- / D-(+)-limonene / dextro-limonene / dextro-para-mentha-1,8-diene / d-limonene / D-para-mentha-1,8-diene / D-p-mentha-1,8-diene / limonene, (R)-(+)- / limonene, D-(+)- / limonene, dextro- / para-mentha-1,8-diene, (R)-(+)- / p-mentha-1,8-diene, (R)-(+)- / p-mentha-1,8-diene,			
--	---	--	--	--

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
	D- / R-(+)-limonen / refchole			

Full text of hazard classes and H-statements : see section 16

\*Chemical name, CAS number and/or exact concentration have been withheld as CBI

\*Contains fixed concentration

### SECTION 4 First-aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
Self protection of the first-aiders	: First aid workers will be equipped with suitable personal protective equipment.

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

### SECTION 5 Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
- Environmental precautions : Avoid release to the environment.

#### 6.2. Methods and materials for containment and cleaning up

- For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.
- For further information refer to section 13.

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Store locked up.
- Packaging materials : Always store product in container of same material as original container.

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment (PPE)

##### Personal protective equipment:

Wear recommended personal protective equipment.

##### Hand protection:

Protective gloves

##### Eye protection:

Safety glasses

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless Light yellow Colourless to light yellow Light yellow to colourless On exposure to air: yellow-brown White White to light yellow On exposure to light: discolours Liquid: colourless Solid: white to brown turns dark coloured Colourless to white Colourless to white-grey Blue-green
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Characteristic odour Lemon odour Mild odour Aromatic odour Cinnamon odour Almond odour Pleasant odour Fruity odour Sweet odour Floral odour Odourless Irritating/pungent odour Asphyxiating odour
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 220 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.994
Density	: 8.304 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 1.837 mm <sup>2</sup> /s @ 40 ° C
Explosive limits	: No data available
Particle characteristics	: No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

### SECTION 11 Toxicological information

#### 11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
LD50 oral rat	> 2000 mg/kg (Rat, Literature study, Oral)
<b>D-Limonene (5989-27-5)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 oral	4400 mg/kg
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Read-across, Dermal, 7 day(s))
LD50 dermal	5000 mg/kg
LC50 Inhalation - Rat	> 5.43 mg/l
ATE CA (oral)	4400 mg/kg bodyweight
ATE CA (Dermal)	5000 mg/kg bodyweight

Skin corrosion/irritation : Not classified

<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
pH	No data available in the literature
<b>D-Limonene (5989-27-5)</b>	
pH	4 (5 %)

Serious eye damage/irritation : Not classified

<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
pH	No data available in the literature
<b>D-Limonene (5989-27-5)</b>	
pH	4 (5 %)

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

<b>D-Limonene (5989-27-5)</b>	
IARC group	3 - Not classifiable

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

<b>D-Limonene (5989-27-5)</b>	
NOAEL (animal/female, F0/P)	600 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

<b>Slick Mist Tire &amp; Trim Shine</b>	
Viscosity, kinematic	1.837 mm <sup>2</sup> /s @ 40 ° C

<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Viscosity, kinematic	No data available in the literature

<b>D-Limonene (5989-27-5)</b>	
Viscosity, kinematic	No data available in the literature

Symptoms/effects after inhalation : None under normal conditions.  
Symptoms/effects after skin contact : May cause an allergic skin reaction.  
Symptoms/effects after eye contact : None under normal conditions.  
Symptoms/effects after ingestion : None under normal conditions.

## SECTION 12 Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
LC50 - Fish [1]	0.97 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	20 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Experimental value)
EC50 96h - Algae [1]	0.017 mg/l Source: Ecological Structure Activity Relationships

<b>Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (82919-37-7)</b>	
LC50 - Fish [1]	0.996 mg/l
EC50 96h - Algae [1]	0.615 mg/l Source: ECOSAR

<b>D-Limonene (5989-27-5)</b>	
LC50 - Fish [1]	720 µg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
LC50 - Fish [2]	702 µg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.31 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Measured concentration)
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna
ErC50 algae	0.32 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Measured concentration)

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>D-Limonene (5989-27-5)</b>	
EC50 72h - Algae [1]	0.32 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.214 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC chronic algae	0.05 mg/l

### 12.2. Persistence and degradability

<b>Slick Mist Tire &amp; Trim Shine</b>	
Persistence and degradability	Not rapidly degradable
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (82919-37-7)</b>	
Persistence and degradability	Not rapidly degradable
<b>D-Limonene (5989-27-5)</b>	
Persistence and degradability	Readily biodegradable in water.
ThOD	3.29 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.37 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
<b>D-Limonene (5989-27-5)</b>	
Bioaccumulative potential	Potential for bioaccumulation ( $4 \leq \text{Log Kow} \leq 5$ ).
BCF - Fish [1]	865 l/kg (BCFBAF v3.01, Pisces, QSAR, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	4.4 (Experimental value, Equivalent or similar to OECD 117, 37 °C)
Partition coefficient n-octanol/water (Log Kow)	4.57

### 12.4. Mobility in soil

<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Ecology - soil	Adsorbs into the soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5.311 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
<b>D-Limonene (5989-27-5)</b>	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3 – 3.8 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 12.5. Other adverse effects

Ozone : Not classified  
Fluorinated greenhouse gases : No

### SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.  
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

### SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
<b>14.1. UN Number</b>			
Not regulated for transport			
<b>14.2. UN Proper Shipping Name</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group, if applicable</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

### 14.6. Special precautions for user

**TDG**  
Not regulated

**DOT**  
Not regulated

**IMDG**  
Not regulated

**IATA**  
Not regulated

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78<sup>9</sup> and the IBC Code<sup>10</sup>

Not applicable

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 15 Regulatory information

#### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (82919-37-7)

Listed on the Canadian DSL (Domestic Substances List)

#### D-Limonene (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Slick Mist Tire & Trim Shine

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (82919-37-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

#### D-Limonene (5989-27-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### SECTION 16 Other Information

Issue date : 06/27/2025  
Revision date : 05/20/2026  
Supersedes : 01/16/2026

#### Full text of hazard classes and H-statements:

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

# Slick Mist Tire & Trim Shine

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

---

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.