

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Issue date: 06/26/2025 Revision date: 05/13/2026 Supersedes: 08/19/2025 Version: 3.1

SECTION 1 Identification**1.1. GHS Product identifier**

Product form : Mixture
Product name : Hot Rod & Classic SAE 10W-40 Motor Oil
Type of product : Lubricating oil
Part Number : 20688

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2 Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS CA)**

Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment, Chronic Hazard, Category 4	H413	May cause long lasting harmful effects to aquatic life.

Full text of H-statements: see section 16

2.2. GHS label elements, including precautionary statements**GHS CA labelling**

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Warning

Hazard statements (GHS CA) : H317 - May cause an allergic skin reaction
H361 - Suspected of damaging fertility or the unborn child
H413 - May cause long lasting harmful effects to aquatic life

Precautionary statements (GHS CA) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

P261 - Avoid breathing vapours.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents and container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	45 - 70*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	30 - 60*	Asp. Tox. 1, H304

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Molybdenum, bis[O,O-bis(2-ethylhexyl)phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo)	Molybdenum, bis[O,O-bis(2-ethylhexyl)phosphorodithioato-S]dioxodi-mu-thioxodi-Molybdenum Diakylidithiophosphate(MoDDP); Oxymolybdenum di-2-ethylhexyl phosphorodithioate, sulfurized; Oxymolybdenum di-2-ethylhexyl phosphorodithioate, sulfurized; Molybdenum, bis[o,o-bis(2-ethylhexyl)phosphorodithioato-ks,ks;Phosphorodithioic acid, O,O-bis(2-ethylhexyl) ester, molybdenum complex; bis[o,o-bis(2-ethylhexyl)phosphorodithioato-s,s']dioxodi-mu-thioxodi-molybdenum; Molybdenum, bis[O,O-bis(2-ethylhexyl)phosphorodithioato-S,S']dioxodi-mu-thioxodi-, (Mo-Mo); Molybdenum, bisO,O-bis(2-ethylhexyl)phosphorodithioato-kappa.S., kappa.Sdioxodi-.mu-thioxodi-, (Mo-Mo) / Oxymolybdenum di-2-ethylhexyl phosphorodithioate, sulfurized	CAS-No.: 72030-25-2	0.5 - 1.5*	Skin Irrit. 2, H315 Skin Sens. 1, H317
Benzenamine, ar-nonyl-N-(nonylphenyl)-	ar-Nonyl-N-(nonylphenyl)benzenamine	CAS-No.: 36878-20-3	0.5 - 1.5*	Repr. 2, H361 Aquatic Chronic 4, H413

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Calcium long chain alkaryl sulfonate	-	CAS-No.: 722503-69-7	0.1 - 1*	Skin Sens. 1, H317

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

*Contains fixed concentration

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Redness. Skin rash/inflammation. Itching. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Evacuate area. Eliminate all ignition sources if safe to do so. Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
- Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material. Move containers from spill area. Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.
- For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Do not breathe vapours. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Keep only in the original container in a cool, well-ventilated place away from: Direct sunlight, Heat sources. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store locked up.
- Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

- Appropriate engineering controls : Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hand protection:
Protective gloves

Eye protection:
Safety glasses

Skin and body protection:
Wear suitable protective clothing

Respiratory protection:
No respiratory protection needed under normal use conditions. [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.86
Density	: 7.1856 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 94.73 mm ² /s @ 40 ° C
Explosive limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE CA (oral)	5000 mg/kg bodyweight
ATE CA (Dermal)	5000 mg/kg bodyweight

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified.

Hot Rod & Classic SAE 10W-40 Motor Oil	
Viscosity, kinematic	94.73 mm ² /s @ 40 ° C

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm ² /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Viscosity, kinematic	12 mm ² /s
Hydrocarbon	Yes

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Redness. Skin rash/inflammation. Itching. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : May cause long lasting harmful effects to aquatic life.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : May cause long lasting harmful effects to aquatic life.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LC50 - Fish [1]	> 0.0013 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.2. Persistence and degradability

Hot Rod & Classic SAE 10W-40 Motor Oil	
Persistence and degradability	Biodegradability in water: no data available.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Persistence and degradability	Not rapidly degradable
Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) (72030-25-2)	
Persistence and degradability	Not rapidly degradable
Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Persistence and degradability	Not rapidly degradable
Calcium long chain alkaryl sulfonate (722503-69-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Hot Rod & Classic SAE 10W-40 Motor Oil	
Bioaccumulative potential	No data available concerning bioaccumulation.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

12.4. Mobility in soil

Hot Rod & Classic SAE 10W-40 Motor Oil	
Ecology - soil	No additional information available.
Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Mobility in soil	35900000 Source: EPISUITE

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

TDG

Not regulated

DOT

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) (72030-25-2)

Listed on the Canadian DSL (Domestic Substances List)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the Canadian DSL (Domestic Substances List)

Hot Rod & Classic SAE 10W-40 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Calcium long chain alkaryl sulfonate (722503-69-7)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Hot Rod & Classic SAE 10W-40 Motor Oil

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) (72030-25-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Calcium long chain alkaryl sulfonate (722503-69-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

SECTION 16 Other Information

Issue date : 06/26/2025
Revision date : 05/13/2026
Supersedes : 08/19/2025

Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Full text of hazard classes and H-statements:

H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H361	Suspected of damaging fertility or the unborn child
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.