

SECTION 1 Identification**1.1. GHS Product identifier**

Product form	: Mixture
Product name	: Emissions Clear
Type of product	: Fuel additives
Part Number	: 20715

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	: Fuel additives
Recommended use	: Fuel additives
Restrictions on use	: No additional information available

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number	: For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.
------------------	---

SECTION 2 Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS CA)**

Flammable liquids, Category 4	H227	Combustible liquid.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Full text of H-statements: see section 16		

2.2. GHS label elements, including precautionary statements**GHS CA labelling**

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Danger

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hazard statements (GHS CA)	: H227 - Combustible liquid H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H318 - Causes serious eye damage H361 - Suspected of damaging fertility or the unborn child
Precautionary statements (GHS CA)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P264 - Wash hands thoroughly after handling. P280 - Wear protective gloves, protective clothing, eye and face protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor. P302+P352 - IF ON SKIN: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice or attention. P310 - Immediately call a POISON CENTER, a doctor. P321 - Specific treatment (see supplemental first aid instruction on this label). P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: Get medical advice or attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO ₂), extinguishing powder to extinguish. P403 - Store in a well-ventilated place. P405 - Store locked up. P501 - Dispose of contents and container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Distillates (petroleum), hydrotreated light	Distillates (petroleum), hydrotreated light distillates (petroleum), hydrotreated light / kerosine - unspecified	CAS-No.: 64742-47-8	60 - 80*	Asp. Tox. 1, H304

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Hexylene glycol	2-Methyl-2,4-pentanediol 2,4-dihydroxy-2-methylpentane / 2,4-Pentanediol, 2-methyl- / 2-methyl-2,4-pentanediol / 2-methylpentane-2,4-diol / hexylene glycol / pinakon	CAS-No.: 107-41-5	15 - 40*	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361
Monoalkylaryl alkoxylate aminated	-	CAS-No.: Undisclosed	7 - 13*	Skin Irrit. 2, H315 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

*Contains fixed concentration

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
First-aid measures general	: Call a physician immediately.
Self protection of the first-aiders	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Risk of lung oedema.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
-------------	-----------------------

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.
For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.
Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.
Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Hexylene glycol (107-41-5)

Canada (Alberta) - Occupational Exposure Limits

Local name	Hexylene glycol
OEL C	121 mg/m ³
	25 ppm

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hexylene glycol (107-41-5)	
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Hexylene glycol
Plafond (OEL C)	121 mg/m ³
	25 ppm
Notations and remarks	RP
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL C	25 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL TWA	25 ppm (V - Vapor fraction)
OEL STEL	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only)
	50 ppm (V - Vapor fraction)
Notations and remarks	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL TWA	25 ppm (V - Vapor fraction)
OEL STEL	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only)
	50 ppm (V - Vapor fraction)
Notations and remarks	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL TWA	25 ppm (V - Vapor fraction)
OEL STEL	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only)
	50 ppm (V - Vapor fraction)
Notations and remarks	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL C	25 ppm

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hexylene glycol (107-41-5)	
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL C	25 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL C	25 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL TWA	25 ppm (V - Vapor fraction)
OEL STEL	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only)
	50 ppm (V - Vapor fraction)
Notations and remarks	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Hexylene glycol
OEL C	25 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 163 °F
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.853
Density	: 7.122 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 3.76 mm ² /s @ 40 ° C
Explosive limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Oxidizing agent.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 oral	15000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID
ATE CA (oral)	15000 mg/kg bodyweight

Hexylene glycol (107-41-5)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Male / female, Experimental value, Oral, 15 day(s))
LD50 oral	3680 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 15 day(s))
LD50 dermal	7900 mg/kg
LC50 Inhalation - Rat	> 55 mg/l (Equivalent or similar to OECD 403, 8 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
ATE CA (oral)	3680 mg/kg bodyweight
ATE CA (Dermal)	7900 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Hexylene glycol (107-41-5)	
NOAEL (oral, rat, 90 days)	450 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : May be fatal if swallowed and enters airways.

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Emissions Clear	
Viscosity, kinematic	3.76 mm ² /s @ 40 ° C
Hexylene glycol (107-41-5)	
Viscosity, kinematic	Not determined
Monoalkylaryl alkoxyate aminated (Undisclosed)	
Viscosity, kinematic	7 mm ² /s
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Risk of lung oedema.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Hexylene glycol (107-41-5)	
LC50 - Fish [1]	9450 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	5410 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 429 mg/l Source: EHCA
EC50 72h - Algae [1]	> 429 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)

12.2. Persistence and degradability

Emissions Clear	
Persistence and degradability	Biodegradability in water: no data available.
Distillates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Not rapidly degradable
Hexylene glycol (107-41-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.02 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.3 g O ₂ /g substance
Monoalkylaryl alkoxyate aminated (Undisclosed)	
Persistence and degradability	Not rapidly degradable

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.3. Bioaccumulative potential

Emissions Clear

Bioaccumulative potential	No data available concerning bioaccumulation.
---------------------------	---

Distillates (petroleum), hydrotreated light (64742-47-8)

Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
---	------------------------

Hexylene glycol (107-41-5)

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
---------------------------	--

Partition coefficient n-octanol/water (Log Pow)	0.58 (QSAR, KOWWIN)
---	---------------------

12.4. Mobility in soil

Emissions Clear

Ecology - soil	No additional information available.
----------------	--------------------------------------

Hexylene glycol (107-41-5)

Ecology - soil	Highly mobile in soil.
----------------	------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0 (log Koc, Calculated value)
--	-------------------------------

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated	NA1993	Not regulated	Not regulated
14.2. UN Proper Shipping Name			
Not regulated	Combustible liquid, n.o.s.(Petroleum Distillates)	Not regulated	Not regulated

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

TDG	DOT	IMDG	IATA
Transport document description			
Not regulated	NA1993 Combustible liquid, n.o.s.(Petroleum Distillates), Comb Liq, III	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Combustible liquid	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	III	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Dangerous for the environment: No	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

TDG

Not regulated

DOT

UN-No. (DOT)

: NA1993

DOT Special Provisions (49 CFR 172.102)

: 148 - Except for transportation by aircraft, when transported as a limited quantity or a consumer commodity, the maximum net capacity specified in §173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx)

: 150

DOT Packaging Non Bulk (49 CFR 173.xxx)

: 203

DOT Packaging Bulk (49 CFR 173.xxx)

: 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

: 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)

: 220 L

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

Emissions Clear

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 15 Regulatory information

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Hexylene glycol (107-41-5)

Listed on the Canadian DSL (Domestic Substances List)

Emissions Clear

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Hexylene glycol (107-41-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Monoalkylaryl alkoxyate aminated (Undisclosed)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16 Other Information

Issue date : 04/14/2025
Revision date : 05/11/2026
Supersedes : 11/14/2025

Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Full text of hazard classes and H-statements:

H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H361	Suspected of damaging fertility or the unborn child

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.